

No: IITMandi(CW)/SE-852/2017-18/290-91

Date: 06-06-2017

### NOTICE INVITING QUOTATION

Sealed item rate quotations as per schedule attached are hereby invited by the undersigned so as to reach in this office on or before 12-06-2017 up to 03:00 PM and shall be opened on the same day at 03:30 PM in the O/o Superintending Engineer, IIT Mandi at Kamand campus in the presence of intending contractor or their authorized representatives.

Name of work: Construction of Cabins of AMRC 2nd floor at Kamand campus.

S.H.-Providing and fixing powder coated Aluminium walls, sliding doors and false ceiling with 12 mm thick Mineral fibre ceiling tiles.

----- As Per Schedule Attached -----

#### Terms & Conditions:-

1. The work will be carried out as per CPWD General Specifications for Civil works amended up to date & as per the instructions of the Engineer-in-charge.
2. The work is of urgent nature and is to be completed within 15 days from issue of work.
3. All damages done during execution of the work is to be made good by the contractor and nothing extra will be paid separately for the same.
4. The Prices quoted should be net and nothing extra is to be paid.
5. Contractor shall abide by labour rules and regulations.
6. All the applicable taxes shall be deducted from bill.
7. All material to be used on the work will have to be got approved from the Engineer-in-charge.

Sd/-  
Dean(I&S)

#### COPY TO:-

1. IIT Mandi website.
2. Notice Board.

Sd/-  
Dean(I&S)

### SCHEDULE OF QUANTITY

Name of work : -Construction of Cabins of AMRC 2nd floor at Kamand campus. S.H.-Providing and fixing powder coated Aluminium walls,sliding doors and false ceiling with 12 mm thick Mineral fibre ceiling tiles.						
Sr. No.	Description of items	Qty.	Unit	Rate(In Rs)		Amount (In Rs)
				(In Figure)	(In Word)	
1	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete as per entire satisfaction and direction of Engineer-in-charge 200x10 mm	4.00	each			
2	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :For fixed portion Powder coated aluminium (minimum thickness of powder coating 50 micron) as per entire satisfaction and direction of Engineer-in-charge	231.49	kg			
3	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron) as per entire satisfaction and direction of Engineer-in-charge	45.89	kg			
4	Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side as per entire satisfaction and direction of Engineer-in-charge	26.90	sqm			
5	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness as per entire satisfaction and direction of Engineer-in-charge	17.93	sqm			
6	Providing and fixing dash fastener for frame work of required lengths as per entire satisfaction and direction of engineer-in-charge as per entire satisfaction and direction of Engineer-in-charge	15.00	each			
7	Providing and fixing Roller set for aluminium door shutter as per entire satisfaction and direction of engineer- in - charge as per entire satisfaction and direction of Engineer-in-charge	2.00	set			
8	Providing and fixing aluminium handle ISI marked powder coated, with necessary screws etc. complete as per entire satisfaction and direction of Engineer-in-charge 200 mm	4.00	each			
9	Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete as per entire satisfaction and direction of Engineer-in-charge	2.00	each			

Sr. No.	Description of items	Qty.	Unit	Rate(In Rs)		Amount (In Rs)
				(In Figure)	(In Word)	
10	<p>Providing and Fixing tiles of size 595 x 595 mm in true horizontal level suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38mm made from 0.33 mm thick (minimum) sheet, spaced 1200mm centre to centre, and cross "T" of size 24x28mm made out of 0.33mm (Minimum) sheet, 1200mm long spaced between main'T' at 600mm centre to centre to form a grid of 1200x600mm and secondary cross 'T' of length 600mm and size 24 x28mm made of 0.33mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600mm panel to from grid of size 600x600mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size(24x24X3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450mm centre to centre with 25mm long dry wall screws @ 230mm interval and laying the tiles in the grid including, cutting/ making opening for services like diffusers, grills,light fittings, fixtures, smoke detectors etc., wherever required, Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6mm fixed to ceiling with 12.5 mm dia and 50mm long dash fasteners, 4mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200mm centre to centre along main 'T' , bottom exposed with 24mm of all T-sections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawings and as directed by engineer-in-charge.</p> <p>Note :- Only tiled false ceiling area will be measured from wall to wall. No deduction shall be made for exposed frames/opening (cut outs) having area less than 0.40 sqm.</p> <p>Mineral Fibre ceiling tiles of Meteor or equivalent finish tile Tegular edge laid on grid of colour white complete as per entire satisfaction and direction of Engineer-in-charge</p>	76.15	sqm			
<b>Total</b>						

sd-  
Dean(I&S)