Indian Institute of Technology Mandi Mandi, Himachal Pradesh - 175075



भारतीय प्रौद्योगिकी संस्थान मंडी मंडी, हिमाचल प्रदेश - 175075

Dated:17-09-2024

No. IITMandi(CW)/SE-1569/2024-25/1624-25

NOTICE INVITING QUOTATION

Sealed item rate quotations as per schedule attached are hereby invited by the undersigned from registered contractors so as to reach in this office on or before 23/09/2024 up to 03:00 PM and shall be opened on the same day at 03:30 PM in the O/o Superintending Engineer, IIT Mandi at Kamand campus in the presence of intending contractors or their authorized representatives.

Name	of	work:	Rectification	work	of	floor	tiles	ઢ	wall	tiles	at	A-10	building,	A-13
building at North Campus of IIT Mandi.														

------ As Per Schedule Attached -----

Terms & Conditions: -

- 1. The work will be carried out as per CPWD General Specifications for **Civil Works** amended up to date & as per the instructions of the Engineer-in-charge.
- 2. The work is to be completed within 21 days from issue of work order.
- 3. Anydamages done during execution of the work/repairs are to be made good by the agency and nothing extra will be paid separately for the same.
- 4. The Prices quoted should be inclusive of all taxes including GST and nothing extra is to be paid.
- 5. Agency shall abide by labor rules and regulations.
- 6. All the applicable taxes shall be deducted from the bill.
- 7. Compensation of delay of work will be @ 0.05% per day.
- 8. GST Registration Certificate should also be attached with NIQ.
- 9. Certificate of enlistment with Central/State Govt. Organization/Central Autonomous body/Central Public Sector Undertaking should also be attached with NIQ.
- All material to be used on the work will have to be got approved from the Engineer-incharge.

Sd/-Superintending Engineer

Copy to:-

- 1. Notice Board.
- 2. Institute Website

Sd/-

Superintending Engineer

Schedule of Quantity

Name of work:Rectification work of floor tiles & wall tiles at A-10 building, A-13 building at North Campus of IIT Mandi.

Sr. No.	Description of Item	Qty.	Unit	Rate(In Rs)		Amount (In Rs)
-				(In Figure)	(In Word)	` '
1	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. A. For thickness of tiles 10 mm to 25 mm	126.00	Sqm			
2	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approvedmake, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.		Sqm			
3	Providing and laying Vitrified tiles in floor in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS:15622, of approved brand & manufacturer, in all colours and shade, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) jointing with grey cement slurry @3.3 kg/sqm including grouting the joints with white cement and matching pigments etc. The tiles must be cut with the zero chipping diamond cutter only . Laying of tiles will be done with the notch trowel, plier, wedge, clips of required thickness, leveling system and rubber mallet for placing the tiles gently and easily. a.Glazed vitrified floor tiles polished finish of size i Size of Tile 600 x 600 mm		Sqm			
4	Providing and laying Vitrified tiles in floor in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS:15622, of approved brand & manufacturer, in all colours and shade, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) jointing with grey cement slurry @3.3 kg/sqm including grouting the joints with white cement and matching pigments etc. The tiles must be cut with the zero chipping diamond cutter only . Laying of tiles will be done with the notch trowel, plier, wedge, clips of required thickness, leveling system and rubber mallet for placing the tiles gently and easily. b.Glazed Vitrified tiles Matt/Antiskid finish of size I .Size of Tile 600 x 600 mm		Sqm			
	Total					

Note:-1. Quoted rate should be inclusive of all applicable taxes including GST(nothing extra shall be payable).

2. All Statutory deduction will be made as per prevailing rates.